

TECHNICAL SPECS / COMMERCIAL, RESIDENTIAL, & HEALTHCARE APPLICATIONS

■ CORE FEATURES

Primary Function	Privacy
Color	White (Off) / Transparent (On)
User Control	Switch, Remote, Voice, Motion
Powered By	Electrical
Privacy	✓
Variable	—
Default / Unpowered State	Private

■ RECOMMENDED APPLICATIONS

Interior / Exterior	✓
Windows	✓
Doors	✓
Skylights	✓
Partitions	✓
Curtainwalls / Glass Walls	✓
Showers	✓
Water Closets	✓

■ CONFIGURATION OPTIONS

Laminated Glass	✓
Insulated Glass	✓
Impact / Attack Rated / Bullet Resistant	✓
Bent	✓
Shapes	✓
Holes	✓
Retrofit / Surface Applied Film	✓

■ SPECIFICATIONS

Operating Voltage	48-65 VAC
Operating Current	20 mA / Sq Ft
Power Consumption	<1w / Sq Ft
Visible Light Transmission	91% (On) / 50% (Off / Private)
Parallel Light	75% (On) / 2% (Off / Private)
Diffused Light	63% (On) / 4% (Off / Private)
UV Blocking	99%
Maximum Size	78" w x 168" h
Minimum Glass Thickness	5/16"
Maximum Glass Thickness	1 1/2"
Response Time	0.1 Sec (On) / 0.4 Sec (Off)
Temperature Limits	14° to 122° F