

CRL Ladder Pulls

- Straight and 'S' Styles Standard
- Optional Designer Finials Available
- Additional Straight and Offset Mid-Posts Available
- For Use With 3/8" to 3/4" (10 to 19 mm) Glass, or 1-3/4" (44 mm) Thick Doors
- 1-1/4" (32 mm) Diameter Heavy Wall 304 Alloy Stainless Steel Tubing
- Brushed and Polished Stainless Steel Finishes
- Custom Finishes and Sizes Available



CRL Ladder Style Pull Handles make even a simple glass door look more elegant and offer eye-catching appeal. Our large variety of standard sizes, along with our ability to rapidly transform stock handles or completely design a new one, makes the CRL Ladder Pull line a one stop shop for you. All our Ladder Pulls, Finials, and Mid-Posts are made from 304 alloy stainless steel to give you years of beauty with easy maintenance.

For additional information or to begin the custom design process, contact CRL Technical Sales at (800) 421-6144 in the U.S., (877) 421-6144 from Canada, or (323) 588-1281 International, and ask for Ext. 7700. You can also email us through our web site at crlaurence.com. From the home page click on Contact Us, and then click on Technical Sales for Commercial Products.

CRL Straight Style Ladder Pulls

- Eleven Sizes Ranging From 24" to 84" (610 to 2134 mm) Overall Height
- Brushed or Polished Stainless Steel

CRL Straight Style Ladder Pulls come with two Mid-Posts and fasteners for mounting back-to-back on 3/8" to 3/4" (10 to 19 mm) thick tempered glass, or on 1-3/4" (44 mm) wood or aluminum doors. Custom Ladder Pulls can be ordered with additional Mid-Posts for added support. Maximum spacing of Mid-Posts is limited to 72" (1829 mm).

- Custom Lengths, Designs, and Finishes Available on Special Order

SPECIFICATIONS:

3/8" to 3/4" (10 to 19 mm) Glass, or 1-3/4" (44 mm) Aluminum or Wood Doors

Construction:

1-1/4" (32 mm) Diameter Stainless Steel Tubing

Glass Fabrication Required:

Two 5/8" (16 mm) Diameter Holes

CAT. NO.	OVERALL LENGTH	MOUNTING HOLES CENTER-TO-CENTER	FINISH
24LPBS	24" (610 mm)	12" (305 mm)	Brushed Stainless
24LPSS	24" (610 mm)	12" (305 mm)	Polished Stainless
30LPBS	30" (762 mm)	18" (457 mm)	Brushed Stainless
30LPSS	30" (762 mm)	18" (457 mm)	Polished Stainless
36LPBS	36" (914 mm)	24" (610 mm)	Brushed Stainless
36LPSS	36" (914 mm)	24" (610 mm)	Polished Stainless
42LPBS	42" (1067 mm)	30" (762 mm)	Brushed Stainless
42LPSS	42" (1067 mm)	30" (762 mm)	Polished Stainless
48LPBS	48" (1219 mm)	36" (914 mm)	Brushed Stainless
48LPSS	48" (1219 mm)	36" (914 mm)	Polished Stainless
54LPBS	54" (1372 mm)	42" (1067 mm)	Brushed Stainless
54LPSS	54" (1372 mm)	42" (1067 mm)	Polished Stainless
60LPBS	60" (1524 mm)	48" (1219 mm)	Brushed Stainless
60LPSS	60" (1524 mm)	48" (1219 mm)	Polished Stainless
66LPBS	66" (1676 mm)	54" (1372 mm)	Brushed Stainless
66LPSS	66" (1676 mm)	54" (1372 mm)	Polished Stainless
72LPBS	72" (1829 mm)	60" (1524 mm)	Brushed Stainless
72LPSS	72" (1829 mm)	60" (1524 mm)	Polished Stainless
78LPBS	78" (1981 mm)	66" (1676 mm)	Brushed Stainless
78LPSS	78" (1981 mm)	66" (1676 mm)	Polished Stainless
84LPBS	84" (2134 mm)	72" (1829 mm)	Brushed Stainless
84LPSS	84" (2134 mm)	72" (1829 mm)	Polished Stainless

Minimum order: 1 each. Sizes and finishes can be combined for quantity pricing. Additional holes required if extra Mid-Posts added (see top right).

