

## COOLVU 55/35 SPEC SHEET

### ■ CORE FEATURES

Primary Function	Tint / Light & Heat Control
Color	Light Tint / Dark Tint (Neutral cool grey)
User Control	No
Powered By	Sunlight
Privacy	No
Variable	✓

### ■ RECOMMENDED APPLICATIONS

Exterior	✓
Windows	✓
Doors	✓
Skylights	✓
Shower Enclosures	No
Curtainwalls / Glass Walls	✓

### ■ CONFIGURATION OPTIONS

Bent	✓
Shapes	✓
Holes	✓
Retrofit / Surface Applied Film	✓

### ■ SPECIFICATIONS

Voltage / Power Consumption	None
Visible Light Transmission	54% (Lightest Tint) - 35% (Darkest Tint)
Solar Heat Gain Coefficient (SHGC)	.43 to .41
Shading Coefficient (SC)	.49 to .46
U Value	1.9
UV Blocking	99%
Maximum Size	60" w x 300" h
Minimum Glass Thickness	N/A
Maximum Glass Thickness	N/A
Response Time	~30 Sec (Darken) / 15 Min (Lighten)
Temperature Limits	N/A

Note: CoolVu specs based on application to 1/4" clear glass. Alternate configurations will yield different results.

**T** 516.777.1100 | **F** 516.777.1106 | **E** info@eGlass.com

Learn more about Innovative Glass and our eGlass® products at [www.InnovativeGlassCorp.com](http://www.InnovativeGlassCorp.com).